

Crossply

	Tread Pattern	Inflated Diameter		Inflated Width		Loaded Static Radius		Rolling Circ. @30 MPH		Revs Per Mile @30 MPH	Max Load	Maximum Pressure		Measuring Rim Width	
		in.	mm.	in.	mm.	in.	mm.	in.	mm.			kg.	psi	bar	in.
6.40-13	C49 T/L	25.12	638	6.38	162	11.61	295	75.12	1908	843	475	30	2.10	4.50	114
5.20-14	D75 T/L	24.02	610	5.24	133	11.18	284	72.24	1835	877	375	30	2.10	3.50	89
5.50-15	C49 T/L	26.25	667	6.10	155	12.50	318	84.82	1994	807	350	30	2.10	4.50	114
5.90h15	Road Speed RS T/L	26.00	660	6.40	163	12.05	306	78.55	1995	807	435	30	2.10	4.50	114
6.40h15	Road Speed RS5	26.89	683	6.85	174	12.52	318	81.45	2069	778	530	30	2.10	4.50	114
6.70h15	Road Speed RS T/L	27.80	706	7.40	189	12.83	326	83.82	2129	756	560	30	2.10	4.50	114
8.00h15	Road Speed RS T/L	29.57	751	8.30	211	13.66	347	89.09	2263	711	632	30	2.10	6.00	152
5.25-16	C18	26.70	709	5.75	146	12.65	321	79.50	2019	797	381	28	1.90	4.00	102
5.50-16	Gold Seal D2/103	27.35	695	6.10	155	12.60	320	81.68	2075	775	406	32	2.20	4.50	114
5.75/6.00-16	C49 T/L	28.35	720	6.75	172	13.50	343	85.75	2178	747	508	30	2.10	5.00	127
6.00h16	Road Speed RS5	27.90	709	6.90	175	13.00	330	84.65	2150	749	450	30	2.10	4.50	114
6.50/6.70-16	C49	29.09	739	6.69	170	13.46	342	85.75	2178	739	532	30	2.10	4.50	114
6.50/6.70h16	Road Speed RS5	28.80	732	7.40	189	13.35	339	87.00	2210	728	572	30	2.10	4.50	114
7.00h16	Road Speed RS5	26.95	685	8.40	213	13.90	353	90.55	2300	700	610	30	2.10	6.00	152
7.50-16	Gold Seal D2/103 T/L	31.45	799	8.45	215	14.75	375	94.29	2395	672	760	36	2.50	6.50	165
4.50-17	C18	26.80	681	4.75	121	12.85	326	88.70	2253	785	406	36	2.50	2.75	70
5.25/5.50-17	Gold Seal D2/103	29.20	742	6.00	152	13.95	354	87.35	2219	725	559	36	2.50	3.25	83
4.75/5.00-18	Gold Seal D2/103	29.00	737	5.40	137	13.75	349	87.00	2210	728	457	36	2.50	3.00	76
5.25/5.50-18	Gold Seal D2/103	30.30	770	6.00	152	14.30	363	90.50	2290	701	559	36	2.50	3.25	83