

Size	Tread Pattern	Inflated Diameter		Inflated Width		Rolling Radius		Revs Per Mile	Max Load		Maximum Pressure		Rimm Diameter	Rimm Width	Rimm Width
		in	mm	in	mm	in	mm		lb	kg	psi	bar			
710X90	Chevron	28.50	724	3.66	93	13.75	349	734	896	406	60	4.20	20.30	2.049	2.69
760X90	Chevron	30.30	770	3.66	93	14.65	372	688	896	406	60	4.20	22.06	2.049	2.69
810X90	Chevron	32.40	823	3.66	93	15.70	399	642	896	406	60	4.20	24.20	2.049	2.69
815X105	Chevron	33.20	843	4.18	106	15.95	405	632	1000	457	65	4.20	24.12	2.550	3.55
875X105	Chevron	35.60	904	4.18	106	17.25	438	585	1008	457	65	4.20	26.55	2.550	3.55
820X120	Chevron	32.60	828	4.77	121	15.65	398	644	1288	584	75	4.20	22.30	2.656	3.54
880X120	Chevron	35.00	889	4.77	121	16.90	429	597	1288	584	75	4.20	24.80	2.656	3.54
895X135	Chevron	34.90	886	5.32	135	16.70	424	604	1680	762	85	4.50	23.25	3.030	3.97
730X130	Chevron	29.16	741	5.31	135	14.10	358	715	780	356	31	2.20	17.75	2.460	3.20
30X3.5	Chevron	31.30	795	3.66	93	15.15	385	665	896	406	60	4.20	23.00	2.049	2.69